


## Bakery Innovations

The best result...


**uni-chains provides the complete solution to all of your conveying needs/problems from dough conveyors to pallet handling. We have developed products that will exceed your expectations whether you need a cleanable belt, a wear resistant chain or a belt to convey a full load of pallets.**



uni Light CR belt



uni SSB 32% open belt



uni Flex SNB-W belt

*Let uni-chains help you increase efficiency and reduce production costs simultaneously.*

### Advantages of uni conveyor chains:

- Less downtime due to higher tensile strength
- High temperature chains
- Longer chain life due to wear resistant materials
- Quick and easy installation with unique locking system
- Safety chains reduce risk of clothes or fingers being caught/trapped
- Increased friction with moulded rubber inserts
- F.D.A. approved materials and U.S.D.A. accepted products (see [www.unichains.com](http://www.unichains.com) for details)

### Advantages of uni modular plastic belt:

- High temperature belts
- Tighter transfer possible with the **new** 25.4 mm pitch uni S-MPB Single Link™
- Quick and easy assembly/disassembly with the new Lockpin
- High tensile strength with reinforced side flexing belts
- Easy to clean Roller Top belt for crate/box accumulation
- Special wear resistant materials increase your belt life
- Low noise belts for pan handling
- F.D.A. approved materials and U.S.D.A. accepted products (see [www.unichains.com](http://www.unichains.com) for details)

www.unichains.com



## Modular plastic belt and conveyor chain solutions for the bakery industry

uni M-SNB M2	uni M-QNB C	uni Light C	uni SNB M2	uni Flex SNB-CR Tight radius	uni Flex SNB-WT Integral moulded edge wearpart
Standard materials: POM-D PP PE	Standard materials: POM-SLF PP PP	Standard materials: POM-LF PP PP PE PA-6	Standard materials: POM-D PP PE	Standard materials: POM-D POM-D PP PP	Standard materials: POM-D POM-D PP PP PA6.6 PA6.6
uni QNB with rubber	uni CNB C	uni S-MPB Single Link™	uni SSB C	uni MPB C	uni MPB Standard Product Support S-types
Standard material: PP Rubber material: Thermolast K, black	Standard materials: POM-D PP PP PE	Standard materials: POM-D PP PE PA6.6	Standard material: PP	Standard materials: POM-I POM-I PP PP PE-I PE-I	Standard materials: POM-D POM-D PP-I PP-I PE PE
uni MPB RO	uni XLB C	uni 802/810	uni 881	uni 820	uni 880/882
Standard materials: POM-I POM-I Roller: POM-I	Standard material: POM-NL	Standard materials: SS304 SS430 S1045	Standard materials: SS304 SS430 S1045	Standard materials: POM-D POM-D POM-LF POM-SLF	Standard materials: POM-D POM-D POM-LF POM-SLF

## Application guidelines

D/LF/SLF/NL-POM • PP-Polypropylene • PE-Polyethylene

Belt/chain style	Belt/chain pitch	Oven infeed and takeaway	Cooling lines	Freezing lines	General conveyance	Raw dough handling	Conditioning	Laminating	Pan handling	Proofer	Pan washing	Metal detectors	Packing lines	Tray conveyance	Box handling	Pallet handling
uni M-SNB M2	12.7 mm		PP/D	PE/D	PP		PP			PP		PE	PP/D	PP/D		
uni M-QNB C	12.7 mm				PP			PP					PP/SLF	PP/SLF		
uni Light C/CR/22%	19.1 mm		D/LF		PP/D	PE	PP	PE/PP		PP		PE	PP/D	PP/D		
uni SNB M2	25.4 mm		D	PE/D	PP/D		PP		D	PP	PP/D	PE	PP/D	PP/D	D	
uni Flex SNB-CR	25.4 mm		PP/D		PP/D				D	PP/D				PP/D	D	
uni Flex SNB-W/WO/WT	25.4 mm	D			PP/D				D	PP/D				PP/D	D	
uni QNB with rubber	25.4 mm								PP					PP	PP	
uni CNB C/18%/22%	25.4 mm		PP/D		PP/D	PE	PP	PE/PP		PP		PE	PP/D	PP/D		
uni S-MPB Single Link™	25.4 mm				PP/D	PE		PE/PP				PE	PP/D	PP/D		
uni SSB C/29%/32%	38.1 mm	LF	LF		PP/LF		PP		LF	PP	PP/LF		PP/D	PP/D	LF	
uni MPB C/18%/20%	50.8 mm		PP/D	PE/D	PP/D	PE	PP	PE/PP	PP/D		PP/D		PP/D		D	
uni MPB RO	50.8 mm								D				D	D	D	
uni XLB C	63.5 mm															NL
uni 802/810/881	38.1 mm	S			S				S							
uni 820/880/882	38.1 mm				LF				LF		LF		LF	LF	LF	