

Meat Innovations

The best result...

uni-chains provides the complete solution to all of your conveying needs/problems from Offal Conveyors to cutting lines and pallet handling. We have developed products that will exceed your expectations whether you need a cleanable belt, a wear resistant chain or a belt to convey a full load of pallets.



uni MPB Single Link™



uni MPB closed belt



uni MPB closed belt

Let uni-chains help you increase efficiency and reduce production costs simultaneously.

Advantages of uni conveyor chains:


- Less downtime due to higher tensile strength
- Longer chain life due to wear resistant materials
- Quick and easy installation with unique locking system
- Safety chains reduce risk of clothes or fingers being caught/trapped
- Increased friction with moulded rubber inserts
- F.D.A. approved materials and U.S.D.A. accepted products (see www.unichains.com for details)

Advantages of uni modular plastic belt:

- Easy to clean, Single Link™ *no brick lay*
- Strong and thick product supports allow more load without breakage
- Quick and easy assembly/disassembly with the new Lockpin
- High tensile strength with reinforced side flexing belts
- Easy to clean Roller Top belt for crate/box accumulation
- More load/longer conveyors with unique sprocket engagement
- Tighter transfer possible with the *new* 25.4 mm pitch uni S-MPB Single Link™
- F.D.A. approved materials and U.S.D.A. accepted products (see www.unichains.com for details)




Modular plastic belt and conveyor chain solutions for the meat industry



uni M-QNB C

Standard materials:


POM-SLF PP PP



uni SNB M2AC

Standard materials:


POM-D PP



uni Flex SNB-CR
Tight radius

Standard materials:

POM-D POM-D
PP PP



uni Flex SNB-WT
Integral moulded
edge wearpart

Standard materials:

POM-D POM-D
PP PP PA6.6 PA6.6



uni QNB with rubber

Standard material:


PP Rubber material:
Thermolast K, black



uni CNB C

Standard materials:


POM-D PE PP PP



uni S-MPB Single Link™

Standard materials:


POM-D PP
PE PA6.6



uni MPB C
uni MPB Single Link™

Standard materials:


POM-I POM-I
PP PP PE-I PE-I



uni MPB-GE

Standard material:

POM-I



uni MPB RO

Standard materials:


POM-I POM-I
Roller: POM-I



uni MPB
Bent Product
Support

Standard materials:


PP-I PE



uni MPB
Standard Product
Support S-types

Standard materials:

POM-D POM-D
PP-I PP-I PE PE



uni MPB
No Cling Product
Support NC-types

Standard materials:


PP-I PP-I PE



uni XLB C

Standard material:

POM-NL



uni 882 TAB/Safety Chain

Standard materials:

POM-LF POM-SLF
POM-D POM-D

Application guidelines

SLF/LF/D/NL-POM • PP-Polypropylene • PE-Polyethylene

Belt/chain style	Belt/chain pitch	Evisceration lines	Offal conveyors	Cutting lines	Deboning lines	Fat/Trim lines	Pacing lines	Elevators/Incline conveyors	Breading conveyors	Shrink wrap conveyors	Tray pack lines	Box/tote handling	Box/tote incline/decline conveyors	Freezers infed/outfeed	Spirals	Pallet handling	General conveyance straight	General conveyance grip	General conveyance radius	Metal detector
uni M-QNB C	12.7 mm									SLF	PP/SLF						SLF			
uni SNB M2AC	25.4 mm									D	D	D		PP/PE			D	PP		PE
uni Flex SNB-L/CR	25.4 mm									D	PP/D	PP/D		D	PP/D				PP/D	
uni Flex SNB-W/WO/WT	25.4 mm									D	PP/D	PP/D	D	D	D				PP/D	
uni QNB with rubber	25.4 mm							PP			PP	PP	PP					PP		
uni CNB C/18%/22%	25.4 mm	D							D								D			PE
uni S-MPB Single Link™	25.4 mm	D	D			D					D						D			
uni MPB C/MPB Single Link™	50.8 mm	PE/D	PE/D	D	D	PE/D	D	PE/D	PE/D	PE/D	D	D	D	PE/D			PE/D			PE
uni MPB-GE	50.8 mm		D					D										D		
uni MPB RO	50.8 mm										D	D								
uni XLB C	50.8 mm															NL				
uni 882 TAB/Safety Chain	38.1 mm										LF	LF	LF							